



PVC軟管

應用

- 軟管/用於液體和氣體的管道
- 管式泵
- 工業清潔：氣動軟管
- 空壓管，冷卻水管，水管
- 供熱用軟管 – 內部輸送水或空氣

特性

- 高彎曲性
- 抗碾壓
- 良好的耐鹼及耐酸性能
- 良好的抗化學性能
- 符合 RoHS 規定

溫度範圍

- -20°C 至 60°C

結構

NORFLEX® 設計

1. 內外壁平滑; 管壁: 柔軟PVC材料

其他產品資訊

- 可提供其它長度及直徑產品
- 透明 (標準)
- 特殊顏色: 全部著色
- 根據客戶要求打標產品

內徑 in / mm	壁厚 mm	外徑 mm	重量 kg/ m	尺寸 長度 m	訂購代碼
- / 2	1,0	4,0	0,012	100	400-9020-0000
1/8 / 3	1,0	5,0	0,016	100	400-9030-0000
- / 4	1,0	6,0	0,020	100	400-9040-0000
- / 4	1,5	7,0	0,034	100	400-9040-2182
- / 5	1,5	8,0	0,040	100	400-9050-0000
1/4 / 6	1,5	9,0	0,046	100	400-9060-0000
1/4 / 6	2,0	10,0	0,065	100	400-9060-2184
- / 7	1,5	10,0	0,052	100	400-9070-0000
5/16 / 8	2,0	12,0	0,082	50	400-9080-0000
- / 9	2,0	13,0	0,090	50	400-9090-0000
3/8 / 10	2,0	14,0	0,098	50	400-9100-0000
- / 12	2,5	17,0	0,148	50	400-9120-0000
- / 14	2,5	19,0	0,168	50	400-9140-0000
- / 15	2,5	20,0	0,178	50	400-9150-0000
5/8 / 16	3,0	22,0	0,233	50	400-9160-0000
- / 18	3,0	24,0	0,257	50	400-9180-0000
- / 20	2,0	24,0	0,180	50	400-9200-0000
- / 20	3,0	26,0	0,282	50	400-9200-2175
7/8 / 22	3,0	28,0	0,306	50	400-9220-0000
1 / 25	3,0	31,0	0,343	25	400-9250-0000
1 1/8 / 30	3,5	37,0	0,479	25	400-9300-0000
1 1/4 / 32	4,0	40,0	0,588	25	400-9320-0000
1 1/2 / 38	5,0	48,0	0,878	25	400-9380-0000
- / 40	4,0	48,0	0,719	25	400-9400-0000
- / 40	5,0	50,0	0,919	25	400-9400-2187
- / 50	5,0	60,0	1,123	25	400-9500-0000
2 3/8 / 60	5,0	70,0	1,327	25	400-9600-0000



禾欣自動化企業社

HoShin Automation Co.,

TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>



附件



CLAMP 208



禾欣自動化企業社

HoShin Automation Co.,

TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>