

# CLAMP 212



## 橋接式管束, 用於連接外部螺旋結構的軟管

### 特性

- 通過特殊的搭橋結構的緊固, 有效防止滲漏
- 固定方式快速且簡便
- 可反復使用的
- 符合 RoHS 規定

### 結構

品質: W2; 管束帶: 不銹鋼 1.4301 = AISI 304; 螺絲: 鍍鋅鋼; 螺帽: 不銹鋼 1.4016 = AISI 430; 橋架: 不銹鋼 1.4301 = AISI 304 (INOX)

### 其他產品資訊

- 可提供其它長度及直徑產品

### 適合的內襯軟管直徑

AIRDUC®: 341 + 345 + 363; 350 (AS/ FOOD-AS / AS BLACK); 351 + 355 (FOOD / INOX FOOD-AS / HT-PUR); 351 + 355 EC; 352 (SE RAILWAY / SE RAILWAY PLUS); 355 AS; 362 (FOOD / EC);

PROTAPE®: 330 (FOOD / BLACK / INOX FOOD -AS); 301 AS; 310 + 320 + 321 + 326 + 327 + 332; 322 EC;  
 CP: 450 + 455 + 457 + 460 + 461 + 465 + 466 + 467 + 476 + 480 + 481 + 483 + 485 + 486 + 487; 450 + 461 PROTECT; 457 + 459 + 465 EC; 471 + 472 + 475 (INOX / INOX EC);  
 TIMBERDUC®: 531 - 533 AS

適合的軟管內徑 d2	緊固範圍 mm	帶寬度	訂購代碼
<b>AIRDUC® &amp; PROTAPE® ≤ 44 mm</b>			
13-16	9-19	5	212-0009-0000
15-18	13-20	5	212-0013-0000
18-26	17-29	5	212-0017-0000
22-28	20-28	5	212-0020-0000
25-29	22-37	9	212-0022-0000
30-35	27-47	9	212-0027-0000
32-37	29-47	9	212-0029-0000
38-44	35-55	9	212-0035-0000
<b>CP Ø 38-65 mm, PROTAPE® TPE 326 MEMORY Ø 51-65mm</b>			
38-45	35-55	9	212-0035-2002
45-50	40-60	9	212-0040-2002
50-55	45-65	9	212-0045-2002
60-65	55-75	9	212-0055-2002
<b>AIRDUC® &amp; PROTAPE® ≥ 45 mm, CP &amp; PROTAPE® TPE 326 MEMORY ≥ 70 mm</b>			
45-50	40-60	9	212-0040-0000
50-55	45-65	9	212-0045-0000
60-65	55-75	9	212-0055-0000
70-75	65-85	9	212-0065-0000
80-85	75-95	9	212-0075-0000
90-95	85-105	9	212-0085-0000
100-105	95-115	9	212-0095-0000
110-115	105-125	9	212-0105-0000
120-125	115-135	9	212-0115-0000
130-135	125-145	9	212-0125-0000
140-145	135-155	9	212-0135-0000
150-155	145-165	9	212-0145-0000
160-165	155-175	9	212-0155-0000
170-175	165-185	9	212-0165-0000



禾欣自動化企業社

HoShin Automation Co.,

TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>

# CLAMP 212

適合的軟管內徑d2	緊固範圍 mm	帶寬度	訂購代碼
180-185	175-195	9	212-0175-0000
190-195	185-205	9	212-0185-0000
200-205	195-215	9	212-0195-0000
210-215	205-225	12	212-0205-0000
220-225	215-235	12	212-0215-0000
230-235	225-245	12	212-0225-0000
240-245	235-255	12	212-0235-0000
250-255	245-265	12	212-0245-0000
260-265	255-275	12	212-0255-0000
270-275	265-285	12	212-0265-0000
280-285	275-295	12	212-0275-0000
285-290	280-300	12	212-0280-0000
290-295	285-305	12	212-0285-0000
300-305	295-315	12	212-0295-0000
310-315	305-325	12	212-0305-0000
320-325	315-335	12	212-0315-0000
330-335	325-345	12	212-0325-0000
340-345	335-355	12	212-0335-0000
350-355	345-365	12	212-0345-0000
360-365	355-375	12	212-0355-0000
370-375	365-385	12	212-0365-0000
380-385	375-395	12	212-0375-0000
390-395	385-405	12	212-0385-0000
400-405	395-415	12	212-0395-0000
410-415	405-425	12	212-0405-0000
430-435	425-445	12	212-0425-0000
450-455	445-465	12	212-0445-0000
470-475	465-485	12	212-0465-0000
485-490	480-500	12	212-0480-0000
500-505	495-515	12	212-0495-0000
510-535	505-545	12	212-0505-0000
520-545	515-555	12	212-0515-0000
550-575	545-585	12	212-0545-0000
580-605	575-615	12	212-0575-0000
600-625	595-635	12	212-0595-0000
630-655	625-665	12	212-0625-0000
650-675	645-685	12	212-0645-0000
675-700	670-710	12	212-0670-0000
700-725	695-735	12	212-0695-0000
730-755	725-765	12	212-0725-0000
750-775	745-785	12	212-0745-0000
800-825	795-835	12	212-0795-0000
825-850	820-860	12	212-0820-0000
850-875	845-885	12	212-0845-0000
880-905	875-915	12	212-0875-0000
900-925	895-935	12	212-0895-0000
925-950	920-960	12	212-0920-0000
950-975	945-985	12	212-0945-0000
975-1000	970-1010	12	212-0970-0000
990-1015	985-1025	12	212-0985-0000
1050-1075	1045-1085	12	212-1045-0000
1080-1125	1075-1135	12	212-1075-0000



禾欣自動化企業社

HoShin Automation Co.,


TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>

# CLAMP 212

## 附件



CONNECT 228



CONNECT 270-271



禾欣自動化企業社

HoShin Automation Co.,

TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>