

CLAMP 217



小孔橋接式管束, 用於連外部螺旋結構的軟管 軟管

- 特性**
- 通過特殊的搭橋結構的緊固, 有效防止滲漏
 - 固定方式快速且簡便
 - 可反復使用的
 - 符合 RoHS 規定
- 結構**
- 品質: W2; 管束帶: 不銹鋼 1.4016 = AISI 430; 螺絲: 鍍鋅鋼; 螺帽: 不銹鋼 1.4016 = AISI 430; 橋架: 不銹鋼 1.4301 = AISI 304 (INOX); 固定圈: 鍍鋅鋼
- 其他產品資訊**
- 可提供其它長度及直徑產品
- 適合的內襯軟管直徑**
- AIRDUC®: 341 + 345 + 363; 350 (AS/ FOOD-AS / AS BLACK); 351 + 355 (FOOD / INOX FOOD-AS / HT / EC); 355 AS; 362 (FOOD / EC);
 PROTAPE®: 326 + 327 MEMORY; 330 (FOOD / AS BLACK / INOX FOOD -AS); 301 AS; 310 + 320 + 321; 322 EC; 332 SE;
 CP: 450 + 455 + 457 + 460 + 461 + 465 + 466 + 467 + 476 + 480 + 481 + 483 + 485 + 486 + 487; 450 + 461 PROTECT; 457 + 459 + 465 EC; 471 + 472 + 475 (INOX / INOX EC);
 TIMBERDUC®: 531 - 533 AS

適合的軟管內徑 d2	緊固範圍 mm	帶寬度	訂購代碼
70-75	65-85	9	217-0065-0000
90-95	85-105	9	217-0085-0000
100-105	95-115	9	217-0095-0000
110-115	105-125	9	217-0105-0000
120-127	115-135	9	217-0115-0000
130-135	125-145	9	217-0125-0000
140-145	135-155	9	217-0135-0000
150-155	145-165	9	217-0145-0000
160-165	155-175	9	217-0155-0000
170-175	165-185	9	217-0165-0000
180-185	175-195	9	217-0175-0000
190-195	185-205	9	217-0185-0000
200-205	195-215	9	217-0195-0000
210-215	205-225	12	217-0205-0000
220-225	215-235	12	217-0215-0000
250-255	245-265	12	217-0245-0000
270-275	265-285	12	217-0265-0000
280-285	275-295	12	217-0275-0000
300-305	295-315	12	217-0295-0000
320-325	315-355	12	217-0315-0000
350-355	345-365	12	217-0345-0000
380-385	375-395	12	217-0375-0000
400-405	395-415	12	217-0395-0000
450-455	445-465	12	217-0445-0000
500-505	495-515	12	217-0495-0000

