



彈性管束保護帶

- | | | |
|--|--|---|
| <p>特性</p> <ul style="list-style-type: none"> • 固定方式快速且簡便 • 可反復使用的 • 高抗磨損 • 良好的耐油，耐汽油，耐化學性能 • 符合 RoHS 規定 <p>溫度範圍</p> <ul style="list-style-type: none"> • -40°C 至 90°C • 短時間可達125°C <p>結構</p> | <p>管壁: 聚氨酯</p> <p>其他產品資訊</p> <ul style="list-style-type: none"> • 可提供其它長度及直徑產品 • 黑色(標準) • 特殊顏色: 全部著色 <p>適合的內襯軟管直徑</p> <p>AIRDUC®: 341 + 345 + 363; 350 (AS/ FOOD-AS / AS BLACK); 351 + 355 + 356 (FOOD / INOX FOOD-AS / EC / HT); 355 + 356 AS; 362 (FOOD / EC);</p> | <p>PROTAPE®: 335 + 371 HT-PVC; 326 + 327 MEMORY; 330 (AS / FOOD / AS BLACK / INOX FOOD-AS); 301 AS; 310 + 320 + 321 + 370 + 371; 322 EC;</p> <p>CP: 450 + 455 + 457 + 460 + 461 + 465 + 466 + 467 + 476 + 480 + 481 + 483 + 485 + 486 + 487; 450 + 461 PROTECT; 457 + 459 + 465 EC; 471 + 472 + 475 (INOX / INOX EC);</p> <p>NORPLAST®: 383 + 388; 385 (AS / C-AS);</p> <p>TIMBERDUC®: 531 - 533 AS;</p> <p>EVA: 373; 373 (AS / EC);</p> <p>NEO: 390 (ONE / TWO);</p> <p>SIL: 391 (ONE / TWO)</p> |
|--|--|---|

適合的軟管內徑d2	訂購代碼
1,5 / 38	228-0038-0000
2 / 50-51	228-0050-0000
2,36 / 60	228-0060-0000
2,5 / 63-65	228-0063-0000
3 / 75-76	228-0075-0000
3,5 / 89-90	228-0090-0000
4 / 100-102	228-0100-0000
4,5 / 114-115	228-0115-0000
5 / 125-127	228-0125-0000
6 / 150-152	228-0150-0000
6,3 / 160	228-0160-0000
6,5 / 165	228-0165-0000
7 / 178-180	228-0180-0000
8 / 200-203	228-0200-0000

我們可提供其他直徑產品。所有指定的數值都是近似值，數字均在20°C攝氏度下取得，會根據實際使用環境情況而變化。請參閱我們的技術附錄 www.norres.com。

附件



CLAMP 212 CLAMP 216 CLAMP 208 CONNECT 270-271