



螺紋接頭

- 應用**
- 食品工業, 製藥工業
 - 真空輸送設備, 真空料斗, 吸入式輸送機, 配料系統
 - 造粒機/壓片機
- 螺紋參考 DIN ISO 228**
- 符合 RoHS 規定
- 溫度範圍**
- -40°C 至 90°C
- 其他產品資訊**
- 可提供其它長度及直徑產品
 - 防氣體及液體滲漏的預先安裝版
- 適合的內襯軟管直徑**
- AIRDUC®: 350 (AS / AS BLACK / FOOD-AS); 351 + 355 + 356 (FOOD / INOX FOOD-AS / EC); 355 + 356 (AS/ HT);
 TIMBERDUC®: 533 AS
- 特性**

額定尺寸 mm	螺紋	重量 千克/個	適合的軟管內徑 d2	訂購代碼
---------	----	---------	------------	------

螺紋接頭 DIN ISO 228; 鋁製品; 請分別選擇軟管和裝配				
25	G1	0,120	ø 25	234-0025-2917
32	G1 1/4	0,160	ø 32	234-0032-2917
38	G1 1/2	0,180	ø 38	234-0038-2917
40	G1 1/2	0,210	ø 40	234-0040-2917
50	G2	0,290	ø 50	234-0050-2917
65	G2 1/2	0,310	ø 65	234-0065-2917
75	G3	0,400	Ø 75	234-0075-2917
80	G3	0,480	ø 80	234-0080-2917
100	G4	0,700	ø 100	234-0100-2917

螺紋接頭 DIN ISO 228; 電鍍鋅鋼絲; 請分別選擇軟管和裝配				
25	G1	0,360	ø 25	234-0025-2918
32	G1 1/4	0,450	ø 32	234-0032-2918
38	G1 1/2	0,520	ø 38	234-0038-2918
40	G1 1/2	0,610	ø 40	234-0040-2918
50	G2	0,850	ø 50	234-0050-2918
65	G2 1/2	0,896	ø 65	234-0065-2918
75	G3	1,000	Ø 75	234-0075-2918
80	G3	1,400	ø 80	234-0080-2918
100	G4	2,030	ø 100	234-0100-2918

螺紋接頭 DIN ISO 228; 不銹鋼 (INOX) 1.4301 (標刻) = AISI 304; 請分別選擇軟管和裝配				
25	G1	0,360	ø 25	234-0025-2919
32	G1 1/4	0,450	ø 32	234-0032-2919
38	G1 1/2	0,520	ø 38	234-0038-2919
40	G1 1/2	0,610	ø 40	234-0040-2919
50	G2	0,850	ø 50	234-0050-2919
65	G2 1/2	0,896	ø 65	234-0065-2919
75	G3	1,000	Ø 75	234-0075-2919
80	G3	1,400	ø 80	234-0080-2919



禾欣自動化企業社
 HoShin Automation Co.,
 TEL:(06)355-9720
 FAX:(06)355-9725
<http://www.auto-matic.com.tw/norres.html>

CONNECT THREAD FITTING 234



額定尺寸 mm	螺紋	重量 千克/個	適合的軟管內徑 d2	訂購代碼
100	G4	2,030	ø 100	234-0100-2919
螺紋接頭 DIN ISO 228; 不銹鋼 (INOX) 1.4404 (標刻) = AISI 316L; 請分別選擇軟管和裝配				
25	G1	0,360	ø 25	234-0025-2920
32	G1 1/4	0,450	ø 32	234-0032-2920
38	G1 1/2	0,520	ø 38	234-0038-2920
40	G1 1/2	0,610	ø 40	234-0040-2920
50	G2	0,850	ø 50	234-0050-2920
65	G2 1/2	0,896	ø 65	234-0065-2920
75	G3	1,000	Ø 75	234-0075-2920
80	G3	1,400	ø 80	234-0080-2920
100	G4	2,030	ø 100	234-0100-2920

可提供其它長度及直徑產品

附件



CONNECT SAFETY
CLAMP ASSEMBLY 231



CONNECT PRESS
ASSEMBLY 232



CONNECT MOULD
ASSEMBLY 233



禾欣自動化企業社
HoShin Automation Co.,
TEL: (06) 355-9720
FAX: (06) 355-9725
<http://www.auto-matic.com.tw/norres.html>