



乳品管道配件，依據DIN 2826/11851

- 應用**
- 食品工業，製藥工業
 - 真空輸送設備，真空料斗，吸入式輸送機，配料系統
 - 造粒機/壓片機
- 特性**
- 符合 RoHS 規定
 - 溫度範圍**
 - -40°C 至 90°C
- 結構**
- 配置: 不銹鋼 1.4301=AISI 304 1.4571 (標刻)= AISI 316Ti; 螺紋適配器使用淡藍色丁腈橡膠 (NBR) 密封, 符合食品安全
- 其他產品資訊**
- 可提供其它長度及直徑產品
 - 防氣體及液體滲漏的預先安裝版
- 適合的內襯軟管直徑**
- AIRDUC®: 350 (AS / AS BLACK / FOOD-AS); 351 + 355 + 356 (FOOD / INOX FOOD-AS)

| 額定尺寸 mm | 內徑 mm | 螺紋 | 重量 千克/個 | 適合的軟管內徑 d2 | 訂購代碼 |
|---|-------|------------|---------|------------|---------------|
| 圓錐接頭 DIN 2826/1151; 不銹鋼 (INOX) 1.4301 (標刻) =AISI 304; 請分別選擇軟管和裝配 | | | | | |
| 25 | 21,00 | RD 52x1/6 | 0,360 | ø 25 | 247-0025-2910 |
| 32 | 28,00 | RD 58x1/6 | 0,440 | ø 32 | 247-0032-2910 |
| 38 | 33,00 | RD 65x1/6 | 0,510 | ø 38 | 247-0038-2910 |
| 40 | 35,00 | RD 65x1/6 | 0,600 | ø 40 | 247-0040-2910 |
| 50 | 44,90 | RD 78x1/6 | 0,840 | ø 50 | 247-0050-2910 |
| 65 | 58,00 | RD 95x1/6 | 1,470 | ø 65 | 247-0065-2910 |
| 75 | 69,60 | RD 110x1/4 | 1,750 | ø 75 | 247-0075-2910 |
| 80 | 73,00 | RD 110x1/4 | 1,950 | ø 80 | 247-0080-2910 |
| 100 | 93,50 | RD 130x1/4 | 2,670 | ø 100 | 247-0100-2910 |
| 螺紋接頭 DIN 2826/11851; 不銹鋼 (INOX) 1.4301 (標刻) =AISI 304; 請分別選擇軟管和裝配 | | | | | |
| 25 | 21,00 | RD 52x1/6 | 0,270 | ø 25 | 247-0025-2912 |
| 32 | 28,00 | RD 58x1/6 | 0,310 | ø 32 | 247-0032-2912 |
| 38 | 33,00 | RD 65x1/6 | 0,350 | ø 38 | 247-0038-2912 |
| 40 | 35,00 | RD 65x1/6 | 0,380 | ø 40 | 247-0040-2912 |
| 50 | 44,90 | RD 78x1/6 | 0,500 | ø 50 | 247-0050-2912 |
| 65 | 58,00 | RD 95x1/6 | 0,850 | ø 65 | 247-0065-2912 |
| 75 | 69,60 | RD 110x1/4 | 0,960 | ø 75 | 247-0075-2912 |
| 80 | 73,00 | RD 110x1/4 | 1,070 | ø 80 | 247-0080-2912 |
| 100 | 93,50 | RD 130x1/4 | 1,410 | ø 100 | 247-0100-2912 |
| 圓錐接頭 DIN 2826/1151; 不銹鋼 (INOX) 1.4571 (標刻) =AISI 316Ti; 請分別選擇軟管和裝配 | | | | | |
| 25 | 21,00 | RD 52x1/6 | 0,360 | ø 25 | 247-0025-2911 |
| 32 | 28,00 | RD 58x1/6 | 0,440 | ø 32 | 247-0032-2911 |
| 38 | 33,00 | RD 65x1/6 | 0,510 | ø 38 | 247-0038-2911 |
| 40 | 35,00 | RD 65x1/6 | 0,600 | ø 40 | 247-0040-2911 |
| 50 | 44,90 | RD 78x1/6 | 0,840 | ø 50 | 247-0050-2911 |
| 65 | 58,00 | RD 95x1/6 | 1,470 | ø 65 | 247-0065-2911 |
| 75 | 69,60 | RD 110x1/4 | 1,750 | ø 75 | 247-0075-2911 |
| 80 | 73,00 | RD 110x1/4 | 1,940 | ø 80 | 247-0080-2911 |



| 額定尺寸 mm | 內徑 mm | 螺紋 | 重量 千克/個 | 適合的軟管內徑 d2 | 訂購代碼 |
|---|-------|------------|---------|------------|---------------|
| 100 | 93,50 | RD 130x1/4 | 2,670 | ø 100 | 247-0100-2911 |
| 螺紋接頭 DIN 2826/11851; 不銹鋼 (INOX) 1.4571 (標刻) = AISI 316Ti; 請分別選擇軟管和裝配 | | | | | |
| 25 | 21,00 | RD 52x1/6 | 0,270 | ø 25 | 247-0025-2913 |
| 32 | 28,00 | RD 58x1/6 | 0,310 | ø 32 | 247-0032-2913 |
| 38 | 33,00 | RD 65x1/6 | 0,350 | ø 38 | 247-0038-2913 |
| 40 | 35,00 | RD 65x1/6 | 0,380 | ø 40 | 247-0040-2913 |
| 50 | 44,90 | RD 78x1/6 | 0,500 | ø 50 | 247-0050-2913 |
| 65 | 58,00 | RD 95x1/6 | 0,850 | ø 65 | 247-0065-2913 |
| 75 | 69,60 | RD 110x1/4 | 0,960 | Ø 75 | 247-0075-2913 |
| 80 | 73,00 | RD 110x1/4 | 1,070 | ø 80 | 247-0080-2913 |
| 100 | 93,50 | RD 130x1/4 | 1,410 | ø 100 | 247-0100-2913 |

所有指定的數值都是近似值，數字均在20°C攝氏度下取得，會根據實際使用環境情況而變化。請參閱技術附錄可提供其它長度及直徑產品

附件



CONNECT SAFETY
CLAMP ASSEMBLY 231



CONNECT PRESS
ASSEMBLY 232



CONNECT MOULD
ASSEMBLY 233



禾欣自動化企業社

HoShin Automation Co.,

TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>