



無菌接頭，依據DIN 11864-1 / DIN 11864-3

應用

- 食品工業，製藥工業
- 真空輸送設備，真空料斗，吸入式輸送機，配料系統
- 造粒機/壓片機

特性

- 符合 RoHS 規定

- REACH according to --> 技術 / 技術資訊 / REACH

溫度範圍

- -40°C 至 90°C

結構

配置: 不銹鋼 1.4404 (標刻) = AISI 316L

其他產品資訊

- 可提供其它長度及直徑產品
- 防氣體及液體滲漏的預先安裝版

| 額定尺寸 | 法蘭盤外徑 | 內徑 | 螺紋 | 重量 | 適合的軟管內徑 d2 | 訂購代碼 |
|---|--------|--------|------------|-------|------------|---------------|
| mm | 法蘭 | mm | | 千克/個 | | |
| Clamp liner DIN 11864-3 sealing form A clamp; 不銹鋼 (INOX)1.4404 (標刻) =AISI 316L; 請分別選擇軟管和裝配 | | | | | | |
| 25 | 50,50 | 26,00 | - | 0,177 | Ø 25 | 249-0025-2926 |
| 32 | 50,50 | 32,00 | - | 0,192 | Ø 32 | 249-0032-2926 |
| 40 | 64,00 | 38,00 | - | 0,320 | Ø 40 | 249-0040-2926 |
| 50 | 77,50 | 50,00 | - | 0,419 | Ø 50 | 249-0050-2926 |
| 65 | 91,00 | 66,00 | - | 0,736 | Ø 65 | 249-0065-2926 |
| 80 | 106,00 | 81,00 | - | 1,028 | Ø 80 | 249-0080-2926 |
| 100 | 130,00 | 100,00 | - | 1,392 | Ø 100 | 249-0100-2926 |
| 夾具適配器帶槽DIN 11864-3密封形式夾具; 不銹鋼 (INOX)1.4404 (標刻) =AISI 316L; 請分別選擇軟管和裝配 | | | | | | |
| 25 | 50,50 | 26,00 | - | 0,150 | ø 25 | 249-0025-2915 |
| 32 | 50,50 | 32,00 | - | 0,180 | ø 32 | 249-0032-2915 |
| 40 | 64,00 | 38,00 | - | 0,190 | ø 40 | 249-0040-2915 |
| 50 | 77,50 | 50,00 | - | 0,340 | ø 50 | 249-0050-2915 |
| 65 | 91,00 | 66,00 | - | 0,400 | ø 65 | 249-0065-2915 |
| 80 | 106,00 | 81,00 | - | 0,450 | ø 80 | 249-0080-2915 |
| 100 | 130,00 | 100,00 | - | 0,330 | ø 100 | 249-0100-2915 |
| DIN11864-1無菌接頭用螺絲或法蘭接頭密封; 不銹鋼 (INOX)1.4404 (標刻) =AISI 316L; 請分別選擇軟管和裝配 | | | | | | |
| 25 | - | 26,00 | RD 52x1/6 | 0,360 | ø 25 | 249-0025-2916 |
| 32 | - | 32,00 | RD 58x1/6 | 0,440 | ø 32 | 249-0032-2916 |
| 40 | - | 38,00 | RD 65x1/6 | 0,360 | ø 40 | 249-0040-2916 |
| 50 | - | 50,00 | RD 78x1/6 | 0,440 | ø 50 | 249-0050-2916 |
| 65 | - | 66,00 | RD 95x1/6 | 1,380 | ø 65 | 249-0065-2916 |
| 80 | - | 81,00 | RD 110x1/4 | 1,900 | ø 80 | 249-0080-2916 |
| 100 | - | 100,00 | RD 130x1/4 | 2,610 | ø 100 | 249-0100-2916 |

所有指定的數值都是近似值，數字均在20°C攝氏度下取得，會根據實際使用環境情況而變化。請參閱技術附錄; 可提供其它長度及直徑產品

附件

禾欣自動化企業社

HoShin Automation Co.,

TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>



CONNECT SAFETY
CLAMP ASSEMBLY
231



CONNECT PRESS
ASSEMBLY 232



CONNECT MOULD
ASSEMBLY 233



禾欣自動化企業社

HoShin Automation Co.,

TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>