



TRI 緊固管束, 用於配套接頭, 符合 DIN 32676

特性

- 固定方式快速且簡便
- 內部螺紋設計可重複使用
- 高抗磨損
- 抗微生物及水解
- 良好的耐油, 耐汽油, 耐化學性能
- 符合 RoHS 規定

溫度範圍

- -40°C 至 90°C

結構

管壁材料: 特殊聚醚聚氨酯 (Pre-PUR®)

其他產品資訊

- 可提供其它長度及直徑產品
- 特殊顏色: 全部著色

適合的內襯軟管直徑

AIRDUC®: 341 + 345; 350 (AS / AS BLACK / FOOD-AS); 351 + 355 + 356 (FOOD / INOX FOOD-AS / EC); 355 + 356 AS;
TIMBERDUC®: 533 AS

額定尺寸 mm	法蘭盤外徑 法蘭	管道內徑 毫米	總計長度 mm	重量 千克/個	適合的軟管內徑 d2	訂購代碼
螺 紋; 適 用 管 型 : 350, 351, 355, 533, 341, 345						
32	50,5	32	60,0	0,060	32	245-0032-8500
38	50,5	38	65,0	0,070	38	245-0038-8500
50	64,0	50	67,0	0,120	50	245-0050-8500
65	91,0	66	67,0	0,180	65	245-0065-8500
80	106,0	81	72,0	0,200	80	245-0080-8500
100	119,0	100	77,0	0,330	100	245-0100-8500
125	155,0	125	91,0	0,480	125	245-0125-8500
150	183,0	150	102,0	0,670	150	245-0150-8500
200	233,5	200	112,5	0,960	200	245-0200-8500
螺 紋; 適 用 管 型 : 356						
32	50,5	32	60,0	0,060	32	245-0032-8501
38	50,5	38	65,0	0,070	38	245-0038-8501
50	64,0	50	67,0	0,120	50	245-0050-8501
65	91,0	66	67,0	0,180	65	245-0065-8501
80	106,0	81	72,0	0,200	80	245-0080-8501
100	119,0	100	77,0	0,330	100	245-0100-8501
125	155,0	125	91,0	0,480	125	245-0125-8501
150	183,0	150	102,0	0,670	150	245-0150-8501
200	233,5	200	112,5	0,960	200	245-0200-8501
預 安 裝; (管 型 請 分 開 選 擇)						
32	50,5	32	60,0	0,060	32	245-0032-8554
38	50,5	38	65,0	0,070	38	245-0038-8554
50	64,0	50	67,0	0,120	50	245-0050-8554
65	91,0	66	67,0	0,180	65	245-0065-8554
80	106,0	81	72,0	0,200	80	245-0080-8554
100	119,0	100	77,0	0,330	100	245-0100-8554
125	155,0	125	91,0	0,480	125	245-0125-8554
150	183,0	150	102,0	0,670	150	245-0150-8554
200	233,5	200	112,5	0,960	200	245-0200-8554



禾欣自動化企業社

HoShin Automation Co.,

TEL:06-3559720

FAX:06-3559725

<http://www.auto-matic.com.tw/index.html>

附件

CONNECT TRI-CLAMP
FITTING 245

